

BEJ-1802


Eco Solvent Printer (With 2 Heads)



Grando Eco Solvent Ink



Two I3200 Heads



* 1.8m Dual I3200 Print Heads Speed

360x1800dpi - 3pass	55 m ² /h
720x1200dpi - 4pass	40 m ² /h
720x1800dpi - 6pass	27 m ² /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.




● Technical Specifications


Model	BEJ-1802	
Print Head	Dual I3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	71.6 in.(1820 mm)
	Thickness	Maximum 59 mil(1.5 mm)
	Weight	132.2 lb.(60 kg)
Printing Width	70.8 in.(1800 mm)	
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank) 6*6 CISS (6 color), 8*8 CISS (8 color) optional
	Color	4 colors (Cyan, Magenta, Yellow, Black) 6 colors, 8 colors optional
Printing Resolution	Maximum 2400 dpi	
Printing Speed	3pass(360x1800dpi): 590 sqft (55 sqm/h)	
	4pass(720x1200dpi): 429 sqft (40 sqm/h)	
	6pass(720x1800dpi): 290 sqft (27 sqm/h)	
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0/LAN	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	128.3(W) x 46.1(D) x 74.1(H) in.	
	3232(W) x 1172(D) x 1884(H) mm	
Weight(with stand)	617.3 lb. (280 kg)	
Package Dimensions	131.8(W) x 29.9(D) x 40.9(H) in.	
	3350(W) x 760(D) x 1040(H) mm	
Package Weight	833.3 lb. (378 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] (68 ℉ [20 ℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



THK high-precision mute rail.



New pinch roller structure of three in group brings more stable feeding precision.



High-precision and high-stability tensioning pulley system.




High quality DC servo motor with good stability and long life.




The automatic cleaning assembly adds a single-way valve to increase the stability of the ink supply.



Infrared heater and cooling fan.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



External power supply, intelligent rolling system