

BEJ-3204


Eco Solvent Inkjet Printer



Grando Eco Solvent Ink



Four I3200-E1 Heads



* 3.2m Four I3200-E1 Print Heads Speed

360x2400dpi - 4pass	100 m ² /h
720x1800dpi - 6pass	75 m ² /h
720x2400dpi - 8pass	50 m ² /h

Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.



● Technical Specifications

Model	BEJ-3204	
Print Head	Four I3200-E1 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	126.7 in.(3220 mm)
	Thickness	Maximum 39.3 mil(1 mm)
	Weight	176 lb.(80 kg)
Printing Width	125.9 in.(3200 mm)	
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	4*4 CISS (220ml ink cartridge with 3L ink tank)
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 2400 dpi	
Printing Speed	4pass(360x2400dpi)	: 100 sqm/h
	6pass(720x1800dpi)	: 75 sqm/h
	8pass(720x2400dpi)	: 50 sqm/h
Media Heating System	Integrated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0/LAN	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	181.4(W) x 38.8(D) x 69.4(H) in.	
	4609(W) x 988(D) x 1763(H) mm	
Weight(with stand)	1543 lb. (700 kg)	
Package Dimensions	Entirety Packing : 188.9(W) x 43.3(D) x 69.6(H) in. (4800(W) x 1100(D) x 1770(H) mm)	
Package Weight	Entirety Packing : 1763.3 lb. (800 kg)	
Environment	Power on	Temperature: 59°F to 90°F (15°C to 32°C) Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41°F to 104°F (5°C to 40°C) Humidity: 20 to 80% (no condensation)
Accessories	Stand, media loading and take-up system, air-cooling system, bulk ink cartridge system, etc	
System Requirement	ADP Required	




THK high-precision mute rail



Automatic moisturizing and cleaning components to ensure cleaning and working stability



High quality DC servo motor has good stability and long service life




Bottom heating added to the printer carriage effectively improves printing stability




Stable 3L bulk system ensures amazing printing speed



Three-foot pinch rollers bring more stable feeding accuracy



Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable power.



External power supply, intelligent rolling system.