


GD-1602

Eco Solvent Printer (with two I3200-E1 heads)



Two I3200-E1 Heads



* 1.6m Two I3200-E1 Print Heads Speed

360x2400dpi - 4pass	43 m ² /h
720x1800dpi - 6pass	30 m ² /h
720x2400dpi - 8pass	21 m ² /h

Grando Eco Solvent Ink




Our range of wide format inkjet printers matches our knack for engineering and quality with your desire for impeccable performance and careless production. You can produce roll-to-roll indoor prints and long term outdoor signs. Wide applications in light box posters, customized car stickers, background wall cloth, label printing, advertising sign, subway advertising, shopping mall advertising signs etc.




● Technical Specifications

Model	GD-1602
Print Head	Two I3200-E1 Print Heads
Printing Technology	Piezoelectric Inkjet
Acceptable Media	Width 210-1650 (mm) Thickness Maximum 39.3 mil(1 mm) Weight 132 lb.(60 kg)
Printing Width	210-1600 (mm)
Ink Cartridges	Type Eco Solvent Ink Capacity Continual Ink Supply System (1.5L ink tank) Color 4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 2400 dpi
Printing Speed	4pass(360x2400dpi) : 43 sqm/h 6pass(720x1800dpi) : 30 sqm/h 8pass(720x2400dpi) : 21 sqm/h
Media Heating System	Integrated post heater & Infrared Dryer & Fan system
Interface	Ethernet Interface
Power	7500W
Power Supply	AC 220V ± 10%, 50/60 HZ
Dimensions(with stand)	108(W)x31(D)x63(H) in. 2750(W)x800(D)x1500(H) mm
Weight(with stand)	661 lb. (300 kg)
Package Dimensions	106(W)x31(D)x30.7(H) in. 2700(W)x790(D)x780(H) mm
Package Weight	771 lb. (350 kg)
Environment	Power on Temperature: 59 ℉ to 90 ℉ [15 ℃ to 32 ℃] / Humidity: 35 to 80% (no condensation) Power off Temperature: 41 ℉ to 104 ℉ [5 ℃ to 40 ℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridge, RIP software etc.




Printer carriage can be moved up and down to adjust print head height




Head cleaning and moisturizing makes operation and maintenance more convenient



High quality DC servo motor has good stability and long service life



Three-foot pinch roller structure brings more stable feeding accuracy




Stable 3L bulk system ensures amazing printing speed



Built-in infrared heater and cooling fan to accelerate the drying of the media



Three stage heating system including pre-heater, print heater, and rear heater and platform vacuum system with adjustable power.



External power supply, intelligent rolling system.