


# GD-5800H


Leather Digital Printer (2/3/4 heads optional)



Grando Eco Solvent Ink



Two DX5 Heads



\* 1.8m Dual DX5 Print Heads Speed

720x720dpi - 4pass	32 m <sup>2</sup> /h
720x1080dpi - 6pass	26 m <sup>2</sup> /h
720x1440dpi - 8pass	20 m <sup>2</sup> /h



Multifunctional printer, using eco solvent ink, ink output is smoother, colorful, unique widening platform and belt system, the material adaptability is more extensive, suitable for some special industry applications and customization!




## ● Technical Specifications

Model	GD-5800H	
Print Head	2-4 DX5 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	71.6 in.(1820 mm)
	Thickness	Maximum 59 mil(1.5 mm)
	Weight	132.2 lb.(60 kg)
Printing Width	70.8 in.(1800 mm)	
Ink Cartridges	Type	Eco Solvent Ink
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank) 6*6 CISS (6 color), 8*8 CISS (8 color) optional
	Color	4 colors (Cyan, Magenta, Yellow, Black) 6 colors, 8 colors optional
Printing Resolution	Maximum 1440 dpi	
Printing Speed	4pass(720x720dpi): 32 sqm/h	
	6pass(720x1080dpi): 26 sqm/h	
	8pass(720x1440dpi): 20 sqm/h	
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	USB 2.0	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	134(W)x37(D)x52(H) in. ( 3400(W)x950(D)x1330(H) mm )	
Weight(with stand)	1543 lb. (700 kg)	
Environment	Power on	Temperature: 59 ℉ to 90 ℉ [15℃ to 32℃] (68 ℉ [20℃] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 ℉ to 104 ℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)
Accessories	USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



THK high-precision mute rail.




High-precision and high-stability tensioning pulley system.



Bulky ink bottle with lack of ink alarm system represents the advanced concept of industrial application.



Automatic moisturizing cleaning assembly ensures the stability of head cleaning and improves working stability.



Unique belt device with suction, wider adaptability, suitable for some specific materials .



Standard configuration anti-static bar can be used to eliminate static electricity. Achieve precise placement of ink dots.



Infrared heater and cooling fan.



External power supply, intelligent rolling system