GD2606-TX / GD3206-TX

Industrial Dye Sublimation Printer (With 6 Heads)





Grando Sublimation Ink

C M Y K

* 3.2m Six I3200 Print Heads Speed

360x1200dpi - 1pass	320 m^2/h
360x2400dpi - 2pass	160 m^2/h
720x1800dpi - 3pass	105 m^2/h

Six I3200 Heads
CMYK



Wide applications in clothing, home decoration fabrics, sampling, shrit, canvas bags, bolster, scooter, flags, textile gadgets etc.






• Technical Specifications (2.6m/3.2m optional)

Model		GD2606-TX(I3200)	GD3206-TX(I3200)
Print Head		Six I3200 Print Heads	Six I3200 Print Heads
Printing Technology		Piezoelectric Inkjet	
Acceptable Media	Width	103 in.(2620 mm)	127.1 in.(3230 mm)
	Thickness	Maximum 39 mil(1 mm)	Maximum 39 mil(1 mm)
	Weight	220 lb.(100 kg)	220 lb.(100 kg)
Printing Width		102 in.(2600 mm)	125.9 in.(3200 mm)
Ink Cartridges	Type	Dye Sublimation Ink	
	Capacity	4*4 CISS (220ml ink cartridge with 3L ink tank)	
	Color	4 colors (Cyan, Magenta, Yellow, Black),8 colors optional	
Printing Resolution		Maximum 2400 dpi	
Printing Speed		1pass(360x1200dpi): 296 sqm/h 2pass(3600x2400dpi): 160 sqm/h 3pass(720x1800dpi): 105 sqm/h	1pass(360x1200dpi): 320 sqm/h 2pass(360x2400dpi): 165 sqm/h 3pass(720x1800dpi): 110 sqm/h
Media Heating System		Intergrated post heater & Infrared Dryer & Fan system	
Interface		USB 3.0	
Power Supply		AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)		158.8(W)x48(D)x73.2(H) in. (4035(W)x1220(D)x1860(H) mm)	167.7(W)x43.3(D)x62.2(H) in. (4620(W)x1100(D)x1580(H) mm)
Weight(with stand)		1320 lb. (600 kg)	1984 lb. (900 kg)
Package Dimensions		167.7(W)x56.8(D)x92.9(H) in. (4260(W)x1445(D)x2360(H) mm)	185.8(W)x47.2(D)x66.1(H) in. (4720(W)x1200(D)x1680(H) mm)
Package Weight		1980 lb. (900 kg)	2094 lb. (950 kg)
Environment	Power on	Temperature: 59℉ to 90℉ [15℃ to 32℃] / Humidity: 35 to 80% (no condensation)	
	Power off	Temperature: 41℉ to 104℉ [5℃ to 40℃] / Humidity: 20 to 80% (no condensation)	
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



Double high-precision mute rail.



Stable 3L bulk system ensures amazing printing speed.



Media retraction tension bar.



Junbo media roll maximum 1000m media load.



Inflatable take up and feed media shaft.



Integrated IR & cooling fan system.



Front expander



Rear media balance bar